


JSR's OLED Materials

Cross-Section Diagram of Top-Emission AMOLED Panel



Material	Status	Performance	
		Market requirements	JSR's Features
Thin Film Encapsurasion (TFE)	Under Development	<ul style="list-style-type: none"> Low WVTR Ink Jet coatability 	<ul style="list-style-type: none"> Based on the technology of "Vitex Systems Inc."
Pixel defining Layer (PDL)	MP	<ul style="list-style-type: none"> High Reliability Wide Range of Taper Angle 	<ul style="list-style-type: none"> Low moisture release and outgassing Available to control taper angle by middle baking process Good planality for PLN Controlability of various characteristics (Refractive Index/Dielectronic constant)
Planarization Layer (PLN)	MP		
Low Temperature Curable Color Resist	Under Development for next generation	<ul style="list-style-type: none"> Deposition without thermal damage to underlayer 	<ul style="list-style-type: none"> Low temperature curable.
Low Temperature Curable Over Coat	Under Development for next generation	<ul style="list-style-type: none"> Deposition without thermal damage for underlayer High Resolution 	<ul style="list-style-type: none"> Low temperature curable. Fine size hole patterning



JSR Corporation

Display Solution Dev.

Next Generation Display Materials Dept.


Tel. +81-3-6218-3570 Fax. +81-3-6218-3693

Http://www.jsr.co.jp

OPTMER™ JEM Series



PDL/PLN Materials for OLED

Taper Control



Taper angle of "JEM Series" can be controlled by adjustment of middle baking condition.

Reliability



"JEM Series" shows lower moisture release and outgassing.



JSR Corporation
 Display Solution Dev.
 Next Generation Display Materials Dept.
 Tel. +81-3-6218-3570 Fax. +81-3-6218-3693
[Http://www.jsr.co.jp](http://www.jsr.co.jp)